



PRODUCT DATA SHEET

15W-40 TRAKTOR OIL

Description

High quality diesel engine oil developed specifically for turbo diesel engines of tractors and combine harvesters.

Applications

Used for turbo diesel engines of agricultural machines including the latest models.

Benefits

- Cleans the engine by preventing deposits with the help of detergent-dispersant additives.
- Helps preventing oil consumption and wear.
- Extends oil change intervals.
- Reduces product range in the filo by its wide application area.
- Helps engine to start easily in cold conditions, provides effective lubrication in hot conditions.
- Creates high film layer at high temperatures with its high Viscosity Index modifiers.

Performance

API CF-4/CF

| TEST | METHOD | TYPICAL PROPERTIES |
|--------------------------------------|-------------|--------------------|
| Density, g/cm ³ , at 15°C | ASTM D 4052 | 0.891 |
| Viscosity, 40 °C, mm ² /s | ASTM D445 | 90 |
| Kinematic Viscosity, cSt, at 100°C | ASTM D 445 | 12,70 |
| Viscosity Index | ASTM D 2270 | 154 |
| Flash Point, °C, min | ASTM D 92 | 235 |
| Pour Point, °C, max | ASTM D 97 | -31 |
| Sulfated Ash % wt. | ASTM D874 | 1,4 |
| Total Base Number, mg KOH/g | ASTM D2896 | 11,7 |