



PRODUCT DATA SHEET

U-W80 TRACTOR OIL

PRODUCT DEFINITION

U-tract SAE W80 Tractor Transmission Oil is a premium multi-purpose fluid designed for year-round service in tractor hydraulic systems, transmissions and PTOs, and differentials with wet brake systems. U-tract SAE W80 Tractor Transmission Oil protects against wear and corrosion of tractor components and has excellent friction properties.

MEETS REQUIREMENTS

ALLISON C3, ALLISON C4API GL-4, Case MAT 3505, FORD M2C-134-A, FORD M2C-134-B, FORD M2C-134-C, FORD M2C-134-D, Ford/NewHolland FNHA-2-C-200.00 (hydraulic oil 134), Ford/NewHolland FNHA-2-C-201.00 (M2C-134D), John Deere J14B, John Deere J14C, John Deere J20A, John Deere J20B, John Deere J20C, John Deere J21A, Komatsu, Kubota UDT, MASSEY FERGUSON M1135, MASSEY FERGUSON M1141, MASSEY FERGUSON M1143, MASSEY FERGUSON M1145, FORD M2C-86-B, FORD M2C-86-C, Steiger SEMS 17001, SAE 80W, Versatile 23M, Versatile 24M, VOLVO VME, White Farm (AGCO) Q-186

TEST	METHOD	TYPICAL PROPERTIES
Density, g/cm ³ , at 15°C	ASTM D4052	886
Kinematic Viscosity, cSt, at 40°C	ASTM D445	58,7
Kinematic Viscosity, cSt, at 100°C	ASTM D445	9,3
Viscosity Index	ASTM D2270	160
Flash Point, °C, min	ASTM D92	>215
Pour Point, °C, max	ASTM D97	-30
TBN (Total base number, mg KOH/g)	ASTM D2896	9,6