

для: Ivan Tara sob

ОТ:KELLY / AIKE POWER

Бесшумная газовая генераторная установка Cummins 1000 кВт в контейнере по следующей цене:

Артикул	Тип	ЦЕНА ЗА ЕДИНИЦУ(RMB)	Qua.	Общая цена(RMB)
1	МОДЕЛЬ: AC1375-NG 1000 КВТ / 1250 КВА ГАЗОГЕНЕРАТОРНАЯ УСТАНОВКА» 230/400V, 50HZ, 1500RPM, 3 PHASE 4 WIRE ПЕРВИЧНАЯ МОЩНОСТЬ : 1000KW / 1250KVA СТАНДАРТНАЯ МОЩНОСТЬ: 1100КВТ / 1375КВА БРЕНД / МОДЕЛЬ ДВИГАТЕЛЯ: Cummins / K50N-G10 МАРКА / МОДЕЛЬ ГЕНЕРАТОРА :STAMFORD/S6L1D-H42 система зажигания:WOODWARD Тихие ящики в контейнерах	1,920,000.00	10	19,200,000.00
Итого 1000 кВт контейнерный бесшумный газовый генератор FOB (Шэньчжэнь/Китай) Цена				19,200,000.00

Remarks:

1. Payment term: 30% deposit via T/T, balance 70% T/T before shipment ;
2. Delivery period: 35-60days after receive the payment for generator;
3. Price validity May 17,2025 ;
4. Warranty: 12 months or 1000 hours running (the earlier one shall prevail) .

Примечания:

1. Срок оплаты: 30% депозит через Т/Т, баланс 70% Т/Т перед отгрузкой;
2. Период поставки: 30-60 дней после получения оплаты за генератор;
3. Срок действия цены 7 мая 2025 года ;
4. Гарантия: 12 месяцев или 1000 часов работы (преобладает более ранний срок).

Kelly,
Phone (+86)18938290904
Email: sales10@aikepower.com

Фотографии следующие:



Тихие ящики в контейнерах



открытая планировка



завод



AC1375-NG

Specifications

Frequency	Voltage	Prime power	Continuous power
50Hz	AC 230/400V		1000kW/1250kVA
Speed	Noise(Open)	Noise(Container)	
1500rpm	≤110dB (A) @7m	≤95dB (A) @7m	

Standard configuration

♦Electronic governor ECU	♦DC24V Charging generator	♦Water tank radiator, cooling fan
♦Ingress protection rating IP23	♦Insulation class H	♦SmartGen HGM6110 controller
♦Air filter	♦Silencers	♦Battery floating charger
♦Battery pack and connection cable	♦Circuit breaker	♦Forklift slot
♦Package: PE film	♦Vibration damper	♦Generator set usage information

Engine parameters

Engine Brand	Cummins
Engine Model	K50N-G10
Engine Speed	1500 rpm
Prime power	N/A
Continuous power	1100kW
Bore×Stroke	159×159 mm
Displacement	50.3L
No. of cylinders	16-V type,4 Cycle
Governor type	ECU
Air Intake method	Turbocharged and Aftercooled
Compression Ratio	11.5:1
Start-up method	DC24V electrical start with charging generator

Gas System

Minimum Fuel Inlet Pressure @ Inlet of GMF Sensor Housing(kPa)				5
Maximum Fuel Inlet Pressure @ Inlet of GMF Sensor Housing(kPa)				20
Maximum Fuel Pressure Variation				+/-1
Acceptable Fuel			Pipeline Quality Natural Gas	
Minimum Fuel Methane Number*—MN				80
Minimum Fuel Energy Content*—BTU/scf(MJ/m³)				800(30)
Gas Consumption (m³ /h)				
Continuous power	100% Load	75% Load	50% Load	25% Load
1100kW	275	214.9	155.5	90.9

Air Intake system

Maximum Allowable Intake Air Restriction	
with Clean Element (kPa)	3.7
with Dirty Element (kPa)	6.2



Cooling system

Coolant Capacity

Engine Only(L)	140
----------------	-----

After-cooler Only(L)	44
----------------------	----

Thermostat (Modulating) Range (°C)	82-93
------------------------------------	-------

Maximum Coolant Temperature into the Aftercooler (°C)	54
---	----

Lubrication system

Oil Pressure

@ Minimum Low Idle (kPa)	138
--------------------------	-----

@ Governed Speed (kPa)	345-483
------------------------	---------

Maximum Allowable Oil Temperature (°C)	121
--	-----

Total System Capacity (Including By-Pass Filter) (L)	234.7
--	-------

Exhaust system

Max. exhaust back pressure (kPa)	10.0
----------------------------------	------

Exhaust gas temperature@ COP100%load(°C)	449
--	-----

Exhaust flow Volume@ COP100%load(L/s)/(CFM)	3151/6677
--	-----------

Alternator parameter

Alternator brand	First all
------------------	-----------

Alternator model	STF1000-1-4
------------------	-------------

Rated output power @400 V (kW/kVA)	1000/1250
------------------------------------	-----------

No. of bearings	1
-----------------	---

Insulation class	H
------------------	---

Voltage Regulation (steady state)	$\leq \pm 1\%$
-----------------------------------	----------------

Ingress protection rating	IP21
---------------------------	------

Coil pitch	2/3
------------	-----

Connection	Three-phase, four-wire
------------	------------------------

Excitation method	Brushless self-excitation
-------------------	---------------------------

Power factor	0.8
--------------	-----

Efficiency	0.95
------------	------

TIF	< 50
-----	--------

THF	$< 2\%$
-----	---------

Control function

Operation function	Power switch, start, stop, emergency stop, closing/opening, etc.
--------------------	--

Controller Model	SmartGen HGM6110
------------------	------------------

Display	132x64 pixel LCD with backlight
---------	---------------------------------

Communication	USB, RS485
---------------	------------

Configurable Inputs/Outputs	4/4
-----------------------------	-----

Ingress Protection Rating	IP65
---------------------------	------

Display function	Phase voltage, line voltage, current, frequency, phase sequence, active power, reactive power, apparent power, power factor, accumulated power generation, engine speed, oil pressure, cooling water temperature, running time, accumulated start-up times, battery voltage, etc.
------------------	---



Protective function	Over-speed, under-speed, over-voltage, under-voltage, over-frequency, under-frequency, over-current, over-power, low oil pressure, high water temperature, low battery voltage, charging failure, etc.
---------------------	--

Power Ratings definitions

Ratings Definitions	Operating condition
Continuous power(COP)	1.Unlimited using time per year. 2.Continuous power is the maximum power available at a constant load factor. 3.No overload capability is allowed.

Size&Weight

	Length/A	Width/B	Height/C	Weight
Open type	5500mm	2300mm	2400mm	11000kg
Container type	6058mm	2438mm	2591mm	14000kg

